

# PETROMERICA

## Full Synthetic ULTRA SAE 10W-40 Motor Oil

**Petromerica Full Synthetic ULTRA SAE 10W-40 Motor Oil** is a superior quality multi-grade motor oil designed with a state-of-the-art low friction additive system for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Petromerica Full Synthetic ULTRA Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile or stationary engines.

**Petromerica Full Synthetic ULTRA SAE 10W-40 Motor Oil** meets or exceeds American Petroleum Institute (API) SN PLUS service classification and is compatible with all prior API categories. Petromerica Full Synthetic ULTRA SAE 10W-40 motor oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A3/B3/B4, MB 229.3, RN 0710/0700, VW 502 00 / 505 00, and many other OEM's specifications where a full synthetic API SN motor oil is recommended.

### Benefits and Applications

- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Full synthetic oil helps to improve fuel economy
- Superior resistance to sludge and varnish deposit formation

### 10W-40 Typical Characteristics - V190117

| SAE GRADE              | Full Syn      | 10W-40      |
|------------------------|---------------|-------------|
| API SERVICE            |               | SN PLUS     |
| API Gravity            | ASTM D4052-11 | 32.08       |
| Flash Point, COC °C/°F | ASTM D92      | 210 / 410   |
| Pour Point, °C/°F      | ASTM D97      | -33 / -27.4 |
| Viscosity @ 40°C, cSt  | ASTM D445     | 97          |
| Viscosity @ 100°C, cSt | ASTM D445     | 15.1        |
| Viscosity Index        | ASTM D2270    | 165         |
| CCS, mPa-sec °C max    | ASTM D5293    | 50.49       |
| Total Base No. TBN     | ASTM D2896    | 9.5         |

Typical test data are average values only.  
Minor variations, which do not affect performance, may occur.

### API SN PLUS

ACEA A3/B3/B4, MB 229.3,  
RN 0710/0700,  
VW 502 00 / 505 00



Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

[www.usglobalpetroleum.com](http://www.usglobalpetroleum.com)

[www.petromericamotoroil.com](http://www.petromericamotoroil.com)